

CIVILTEC

HEAVY DUTY DWV SOLVENT WELD



PLASTEC
INNOVATIVE PLUMBING SOLUTIONS



Plastec introduces a new, extensive range of Heavy Duty DWV fittings. Designed thick to withstand stress and last a lifetime.

- 5mm wall thickness for 100mm and 6mm wall thickness for 150mm
- Comparable to a SN22 stiffness rating
- Ideal for drains in reactive and unstable soil
- Support gussets on junctions and IO's



15° FxF Bend



ID	Ø	Box
21168	100	31

15° MxF Bend



ID	Ø	Box
21168	100	31

45° FxF Bend



ID	Ø	Box
19334	100	26
19331	150	12

43° MxF Bend



ID	Ø	Box
18781	100	30
18842	150	12

60° FxF Bend



ID	Ø	Box
19489	100	31

60° MxF Bend



ID	Ø	Box
20702	100	31

88° FxF Bend



ID	Ø	Box
19335	100	18
19332	150	8

Inspection Opening FxF



ID	Ø	Box
19324	100	14
19327	150	7

Level Invert Taper



ID	Ø	Box
19330	100x150	20

45° FxF Junction



ID	Ø	Box
19321	100	12
19322	150	5

43° MxF Junction



ID	Ø	Box
19622	150	8

Junction 150x100x45° FxF



ID	Ø	Box
19323	150	5

Junction 150x100x45° MxF



ID	Ø	Box
19623	150	7

88° FxF Junction



ID	Ø	Box
19499	100	12
20912	150	5

Riley Junction Solvent Weld



ID	Ø	Box
20815	150	4

Civiltec Threaded Adaptor



ID	Ø	Box
20584	150	8

Manhole Access Bend Internal



ID	Ø	Box
20041	150	4

Manhole Access Bend Threaded



ID	Ø	Box
20099	100	12
20097	150	5



PLASTEC
INNOVATIVE PLUMBING SOLUTIONS

Phone: (07) 5413 4444
Email: sales@plastec.com.au
www.plastec.com.au

